

4CH Real-Time

SA-4100HDE+

SA-4100HDX+



Front Panel



Rear Panel



SA-4100HDX+

SPECIFICATIONS		MODEL	
		SA-4100HDE+	SA-4100HDX+
System	Compression Format	Baseline H.264	
	OS	Embedded Linux	
Video	Input	4CH,BNC(1.0Vp-p,75Ω)	
	Standard Output	VGA CVBS	
	Advanced Output	HDMI,Spot	
Audio	Audio Input	4CH	2CH
	Audio Output	1CH	
	Two Way Audio	YES	
Recording	Real Time Recording	4CH D1 Real time	
	HD-SDI	NO	
	D1	120(NTSC)/100(PAL)fps	
	CIF	120(NTSC)/100(PAL)fps	
	Recording Mode	Schedule ,Manual, Montion, Sensor	
Playback	Playback Channel	4CH	
	Search Mode	Time ,Event,File Mangement,Image(snapshot)	
Backup	USB Disk	1 USB 2.0 port	
	DVD Burner	Optional	
Remote Application	Backup Format	DAT or AVI	
	Dual Stream	Master stream :1~25/30fps@ CIF Network stream:1~12/15fps@CIF	
	Browser	IE(Windows XP /2000/vista/9),Safari(Mac OS)	
	CMS	YES	
	3G	Super Live pro/HD for iPad2/iPhone/Blackberry/Android/Symbian/Windows mobile	
Alarm	Alarm Input	4CH	NO
	Alarm Output	1CH	NO
Storage	HDD	1	
	e-SATA	NO	
PTZ	PTZ	1*RS485	
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP,VISCA,SAMSUNG,RM110,HY	
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)	
	Protocol	TCP/IP,DHCP,DDNS,NTP,SMTP	
Others	Dimension	W300xD260xH55mm	
	IR Controller	x1, with IR exstention option	
	Power Supply	DC 12V/2A	