



FEATURES:

- Built in Mini microphone
- Audio output covered 10M
- Back light compensation
- Auto White balance
- Support AC/VIDEO Auto iris Lens

| | |
|-------------------------|--|
| Model | BX-322CS |
| Image Sensor | 1/3 Super Had CCD |
| DSP System | SONY DSP Chipset |
| TV System | NTSC / PAL |
| Effective Pixels | NTSC:510(H) x 492(V) PAL:500(H) x 582(V) |
| Scanning Area | 4.9mm x 3.7mm |
| Horizontal Resolution | 420 TV Lines |
| Minimum Illumination | 0.2 Lux / F1.2 |
| Lens Mount | C/CS Mount |
| S/N Ratio | More than 48dB |
| Electronic Shutter | 1/50 ~ 1/120,000 sec |
| Auto Iris Control | VIDEO/DC Selectable |
| Gamma Modification | 0.45 |
| Gain Control | Auto |
| White Balance | AWB |
| Synchronous System | Internal |
| Back Light Compensation | On/off switchable |
| Video Output | 1.0Vp p composite video signal 75 Ω |
| Operating Temperature | -10°C to 50°C |
| Power Supply Voltage | DC 12V |
| Power Consumption | 180mA |
| Dimensions W x D x H | 60 x 110 x 55mm |
| Weight | 330g |

