

IR VARI-FOCAL VANDAL-PROOF DOME CAMERA

DAI-390IPVF



Sony Exmor IMX122 1/3" CMOS
2 Mega-Pixel
True Day & Night (IR Cut Removable)
0 Lux (IR On) Min. Illumination
ONVIF
Digital WDR

3D Noise Reduction
BLC/HLC
Motion Detection and Privacy Masking
3.3-12mm Vari-Focal Lens
25m IR Illumination

PoE Support
Local Storage
RS-485
I/O – 1 Alarm in / 1 Alarm Out
2 Way Audio
IP 66 Protection
Vandal-Proof

Specifications

Camera	Video	Model	DAI-390IPVF
		Image Sensor	Sony Exmor IMX122 1/3" CMOS
		Effective Pixels	1920x1080
		Electronic Shutter	1/25s ~ 1/100000s
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G711A
		Communication	Two Way Audio
		Image Enhancement	Image Settings
	WDR Range		Digital WDR
	Noise Reduction		3D-DNR
	Image Orientation		Mirror/Flip
	Privacy Zone		Yes
	Motion Detection		Yes
	Compression	Video Compression	H.264
Resolution		1080P (1920x1080), 960P (1280x960), 720P (1280x720), VGA, QVGA	
Multi-stream		1920x1080 (1~30fps) / 1280x960 (1~30fps) / 1280x720 (1~30fps) / 1280x720 (1~30fps) / 640x480 (1~30fps) / 320x240 (1~30fps)	
Bit rate		64Kbps ~ 8Mbps	
Encode Mode		VBR/CBR	
Image Quality		Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	25m (30 IR LED)
	Lens	3.3-12mm
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Water-proof	IP66
	Bracket	3-Axis Gimbal
	Dimensions	Φ150mm×114mm
Connectivity	Weight(gross)	880g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNCx1)
	Mic Connectivity	1Ch Input, 1Ch Output
	SD Card	Support TF (64GB Max)
	RS485	Yes
	Alarm	1Ch Input, 1Ch Output
	Remote Monitoring	IE Browsing, CMS 2.0 Control Software
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
Network	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/PoE
	Work Environment	-10 C ~50 C, 10%~90% Humidity

