

30M VARI-FOCAL

I3-325CSVF
I3-370CSVF



Available with 2.8-12mm lens



* Functionality is subject to camera model

- Prestigious aluminum case
 - Indoor & Outdoor Applications
 - Day & Night Function
 - Bracket Included
 - Visible IR Distance 30 M
 - Waterproof capability
- I3-325CSVF**
- 1/3 SONY CCD
 - 420 TVL resolution
 - Auto White Balance
- I3-370CSVF**
- SONY EFFIO-E
 - 1/3 CCD 650 TVL
 - 2D Noise Reduction
 - OSD Menu
 - Motion Detection and Privacy Masking
 - Color Rolling Control
 - BLC/HLC/AGC
 - ATR (Adaptive Tone Reproduction)

Specifications

MODEL	I3-370CSVF	I3-325CSVF
Image Sensor	1/3" Sony DS CCD (PAL:ICX673AK/NTSC:ICX672AK)	1/3" Sony CCD (PAL:ICX633BK/NTSC:ICX632BK)
DSP System	CXD4140	CXD3142
Effective Pixels	PAL:976(H)x582(V) NTSC:976(H)x494(V)	PAL:537(H)x597(V) NTSC:537(H)x505(V)
Scanning System	PAL/NTSC	PAL/NTSC
Horizontal Resolution	650TVL	420TVL
Min. Illumination	0.03 Lux / F1.0 (0 Lux IR On)	0.5 LUX (0 Lux IR On)
IR LED	36 PSC (30mt)	
OSD Menu	Available(7 languages)	Not Available
Backlight Compensation	BLC/HLC/OFF selectable	Not Available
Sync. System	Internal	Internal
S/N Ratio	≥48db (AGC Off)	48db (AGC Off)
White Balance	Atw/Push/User /Anti CR/Manual	Auto (AWB)
Gamma Correction	0.45	0.45
Gain Control	Yes	Auto (AGC)
Motion Detection	On/Off(4 Zone)	Not Available
Privacy Masking	On/Off(4 Zone)	Not Available
Mirror(H-REV)	On/Off	Not Available
SHARPNESS	On/Off (Level Adjustable)	Not Available
D/N Selection	Color/B/W/Auto	Not Available
ATR	On/Off	Not Available
Noise Reduce	2D-DNR	Not Available
Picture Adjustment	Yes	Not Available
Analog Output	Composite, BNC (1.0Vp-p.75hm)	
Lens	2.8-12 /4-9mm Vari-Focal	
Power	DC 12V / 430mA	
Dimension	195L x 78W x 175H mm	
Net Weight	810G	

