

HIDDEN

INFRA RED PIR CAMERA

IV-425CS
IV-322CS
IV-352CS



Features

- Built-in Hidden IR Leds
- 18 IR Leds for 10mt
- For Day & Night Conditions
- Miniature Hidden camera
- Built-in Pin-Hole Lens
- Auto White Balance



Specifications

MODEL	IV-352CS	IV-322CS	IV-425CS
Image Sensor	1/3" Sony CCD (PAL:ICX639BK NTSC:ICX638BK)	1/3" Sony CCD (PAL:ICX633BK NTSC:ICX632BK)	1/4" Sony CCD (PAL:ICX643BK NTSC:ICX642BK)
DSP System	CXD3172	CXD3142	
TV System	PAL/NTSC		
Effective Pixels	PAL:795(H)x596(V) NTSC:811(H)x508(V)	PAL:537(H)x597(V) NTSC:537(H)x505(V)	
Horizontal Resolution	540TVL	420TVL	
Minimum Illumination	0.05 LUX	0.1 LUX	0.5 LUX
S/N Ratio	48db (AGC Off)		
Video Output	Composite, BNC (1.0Vp.p 75 hm)		
White Balance	Auto (AWB)		
Gain Control	Auto (1/50 ~ 1/120000 Sec.)		
Backlight Compensation	Adjustable		
Electronic Shutter	Auto (AGC)		
Gamma Correction	0.45		
Sync. System	Internal		
IR LED	18 PSC		
IR View Distance	10m		
Lens	3.7mm Pinhole lens		
Power	DC12V/180mA		
Operation Temperature	-10°C ~ 50°C		
Dimension	33L x 60W x 104H mm		
Net Weight	110g		

